

SIGLINK

Temperature & Humidity sensor



- *Simple, cheap and easy to use*
- *Compact design*
- *Long battery life*
- *Replaceable battery*
- *Adjustable transmission period*
- *Compatible with IoTpool platform*

FIRMWARE

MODIFICATIONS

On customer request we can provide tailored firmware modifications. For example, changing data format, implementing data log, inbuilt alarms, etc.

USE EXAMPLES

Indoors (home comfort)

Baby rooms

Greenhouses

Server rooms

Warehouses

Office comfort

Cigar storage

Wine cellars

MANUFACTURER

The product was designed and manufactured in the Czech Republic by IoT Global Solutions, a company dedicated to providing innovative IoT solutions.

CONTACT

info@iot-gsolutions.com

www.iot-gsolutions.com

Should you have any queries, please feel free to contact us.

Technical details

Sensor type:	Temperature and humidity sensor
Dimensions:	71 x 71 x 27 mm
Weight:	80 g (including battery)
Color options:	White, black, grey
Installation:	Vertical
IP rating:	IP40

Power supply:	Replaceable Li-SOCI2 AA battery 3.6 V, 2200 mAh
Battery life:	2–5 years depending on transmission period

Temperature accuracy:	±0.2 °C
Humidity accuracy:	±2 % RH
Operating temperature:	-30 / +80 °C

Network:	SIGFOX, zone RC1
Frequency:	868.13 MHz